



V100P Ordering Codes:

1. **Positioner:** V100P
2. **Spindle (Drive):** D__*
3. **Front Cover:**
 - 90 degree
 - 60 degree
 - 45 degree
 - 30 degree
 - 00 blank
4. **Indicator**
 - A – arrow
 - B – raised indicator/beacon
5. **Cam:** C__**

Example Ordering Code: **V100P-D1-90-A-C1**

Description: Pneumatic positioner with namur drive, standard 90 degree cover, standard arrow indicator and standard 90 degree cam.

** (See spindle and cam selections below)

*Spindles (Drive):

- D1 Namur – Standard
- D2 1/2" Square
- D3 DeZurik Powerac
- D4 Round – Linear
- D5 Double D
- D6 DeZurik Diaphragm/T-Box
- D7 3/4" Slotted
- D8 12mm Dual Post
- D9 Bray – Old Style
- D11 Octagon
- D12 DeZurik Special

**Cams:

- C1 90° & 180°, Linear 0-100
- C2 45° & 90°, Linear 0-100
- C3 30° & 60°, Linear 0-100
- C4 60° & 120°, Linear 0-100
- C5 90° & 60°, Pin 0-100
- C6 90° & 60°, Slot 0-100
- C7 90°, Square Root 0-100
- C8 90°, Equal Percent
- C9 70°, Linear with 35° Zero suppress
- C10 90°, 4-way (25°) split range

Options:

- W1- Low gain pilot valve
- W2- High gain pilot
- NIC- nickel coating
- Gauges
- 24 PSI range spring
- ** All positioners are shipped standard with W3 medium gain pilot. ***