



Ordering Codes

Positioner	Spindle	Front Cover	Indicator	Cam	Coating
V200P/E (IS)	D____*	90 90 Degree 60 60 Degree 45 45 Degree 30 30 Degree 01 Blank	A Arrow B Beacon	C____*	TUF

*See spindle and cam selection below

Standard Spool valve shipped is SG/LB (standard gain/low bleed) see below options

Example: V200E-D2-90-B-C1-TUF

V200 electropneumatic positioner with 1/2" square spindle, standard 90 degree cover, beacon indicator, and standard 90 degree cam, Tuftram® coated.

* Spindles

D1	Namur		D8	12 mm Dual Post
D2	1/2" Square		D9	Old Namur
D3	3/8" Square		D10	Namur-special-long
D4	Round (Linear)		D11	Octagon
D5	Double D		D12	DeZurik special
D6	3/8" Square-long		D15	Namur slotted special
D7	3/4" Slotted		D17	Bailey positioner equal

* Cams

C1	90° & 180°, Linear + split range		C6	90° & 60°, Slot 0-100
C2	45° & 90°, Linear 0-100		C7	90°, Square root 0-100
C3	30° & 60°, Linear 0-100		C8	90°, Equal %
C4	60° & 120°, Linear 0-100		C9	70° Linear with 35° zero suppress
C5	90° & 60°, Pin 0-100		C10	90°, 4 way 25°, split range
			C11	270° Linear

Options:

High Gain Spool Valve	HG
Super High Gain/High Flow Spool Valve	SHG/HF
Beacon Indicators-Yellow/black or Red/green.	

Gauges-must specify quantity and pressures gauge options

NOTE: Tuftram coating available in V200P or E (IS) only-no external lps are Tuftram coated.