



VALVE ACCESSORIES & CONTROLS, INC.

Positioner	Spindle	Front Cover	Indicator	Cam	Special Ip
V200E	D____*	90 90 Degree 60 60 Degree 45 45 Degree 30 30 Degree 00 Blank	A Arrow B Beacon	C____*	GA-Gas Approved

*See spindle and cam selection below

Example: V200E-EX-D2-90-B-C-GA

V200 electropneumatic, 4/20 mA (explosion proof-gas approved), with 1/2" square spindle, standard 90 degree cover, beacon indicator, and standard 90 degree cam.

* Spindles

D1 Namur	D8 12 mm Dual Post
D2 1/2" Square	D9 Old Namur
D3 3/8" Square	D10 Namur-special-long
D4 Round (Linear)	D11 Octagon
D5 Double D	D12 3/8" square extra long
D6 3/8" Square-long	
D7 3/4" Slotted	

* Cams

C1 90° & 180°, Linear + split range	C6 90° & 60°, Slot 0-100
C2 45° & 90°, Linear 0-100	C7 90°, Square root 0-100
C3 30° & 60°, Linear 0-100	C8 90°, Equal %
C4 60° & 120°, Linear 0-100	C9 70° Linear with 35° zero suppress
C5 90° & 60°, Pin 0-100	C10 90°, 4 way 25°, split range

Options:

High Gain Spool Valve	HG
Super high gain/flow	SHGHF

Gauges-must specify quantity and pressures