



VALVE ACCESSORIES & CONTROLS, INC.

Positioner	Spindle	Front Cover	Indicator	Cam
V200E-IS-	D _____*	90 90 Degree	A Arrow	C _____*
		60 60 Degree	B Beacon	
		45 45 Degree		
		30 30 Degree		
		00 Blank		

*See spindle and cam selection below

Example: V200E-IS-D1-90-A-C1

Electropneumatic , intrinsically safe V200 positioner with namur spindle, standard 90 degree cover, arrow indicator, and standard 90 degree cam.

* Spindles

D1 Namur	D8 12 mm Dual Post
D2 1/2" Square	D9 Old Namur
D3 3/8" Square	D10 Namur-special-long
D4 Round (Linear)	D11 Octagon
D5 Double D	D18 8 mm Single D
D6 3/8" Square-long	D19 8 mm Single D Threaded
D7 3/4" Slotted	Other Spindle options available,contact VAC

* Cams

C1 90° & 180°, Linear + split range	C6 90° & 60°, Slot 0-100
C2 45° & 90°, Linear 0-100	C7 90°, Square root 0-100
C3 30° & 60°, Linear 0-100	C8 90°, Equal %
C4 60° & 120°, Linear 0-100	C9 70° Linear with 35° zero suppress
C5 90° & 60°, Pin 0-100	C10 90°, 4 way 25°, split range

Options:

High Gain Spool Valve	HG
Super High Gain High Flow	SHGHF

Internal positioner feedback is not available in IS models.

Externally mounted feedback options available, please contact VAC.