



## Technical Specifications

### V200P EHT (Extra High Temp) Pneumatic Positioner

Available in pneumatic only.

Input range:	3-15 PSI	20-100 kPa
Supply pressure:	145 PSI	<1 MPa
Linearity error:	<1.0 f.s.	
Hysteresis:	<0.5 f.s.	
Repeatability:	<0.4 f.s.	

<b>Pneumatic Flow</b>	<b>Standard/Low Bleed</b>	<b>High Gain</b>	<b>Super High Gain/High Flow</b>
Pressure Gain: @87 PSI (600kPa) acc.to ISA S75.13	240:1	1100:1	1100:1

Air Delivery: @87 PSI (600kPa)	SCFM 28.3	31.8	50.0
-----------------------------------	--------------	------	------

Air Consumption: @87 PSI	SCFM <.2	.71	1.3
-----------------------------	-------------	-----	-----

Temp Range:	-40° to 325° Fahrenheit -40° to 163° Celsius
-------------	---

Temperature Effect:	Zero 1.5% @ 325F Span 6.0% @ 325F
---------------------	--------------------------------------

The above is based on calibrating at ambient temperature and the unit subjected to 325F.

Air Connections:	¼" NPT or G Threads
Gauge port:	⅛" NPT or G Threads

Ingress & corrosion protection:	Nema 4X and IP 66
Coating:	Nickel Plated-Aluminum

Weight	3.5 lbs	1.6 kg
--------	---------	--------